



Features

- 2.8mm-12mm motorized lens
- High Definition TVI 1080P real-time video
- HD TVI video output, no delay, lossless, long distance transmission
- Reach 400 meters coaxial cable real-time transmission
- Automatic Sensor-up function
- S/N ratio more than 50dB (AGC Off)
- No ghosting when moving
- Excellent pixel technology
- The lowest random noise
- Stable black level and long endurance
- OSD

Specifications

CAMERA	
Sensor	1.2.7 CMOS
Signal System	NTSC / PAL
Effective Pixels	1920H x 1080V
Min. Illumination	0 LUX when IR on
IR LED	30 Units
Video Output Level	1.0Vp-p / 75Ω
Horizontal Resolution	2 Megapixel / 30fps
S / N	More than 50dB (AGC off)
White Balance	ATW / AWC / MANUAL / PUSH
Lens	2.8mm-12mm motorized
In / Out Connector	Power (Red Jacket), Video (Yellow Jacket)
GENERAL	
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60 °C)
Operating Humidity	10%-85% RH
Power	12 VDC
Power Consumption	Less than 1000mA
Dimensions	φ5.5" x 4.3" (H) (φ14cm x 11cm(H))
Unit Weight	0.85lb (.385kg)
Shipping Weight	1.10lb (0.498kg)