

VR-5B-8E-4

Essential 4 Channel Digital Video Recorder



VEILUX[®]
The Art of Surveillance



Features

- 4-channel BNC input
- Up to 4MP resolution for recording
- Holds up to 2x HDD or (1x HDD + 1x eSATA)
- H.265, H.264, JPEG video compression
- Supports ONVIF
- 2x USB 2.0 and 2x RS485

Specifications

VIDEO/AUDIO INPUT	
Input	4 BNC
Input Resolution	8MP, 4MP, 3MP, 2MP, 960H
Output	1 HDMI / 1 VGA / 2 BNC (1 HD / 1 SD)
Output Resolution	4K, FHD, SXGA, XGA
RECORDING	
Speed	15fps/ch(4MP), 30fps/ch(2MP)
Resolution	8MP, 4MP, 3MP, 2MP, 960H
AUDIO	
Input	4 RCA
Output	1 HDMI, 1 RCA
INTERFACE	
Sensor In/Out	4/1 - NC/NO
USB	2 x USB 2.0
PTZ/Keyboard	2 x RS485 - Terminal Block
ATM /POS	Ethernet POS
NETWORK	
Interface	2 x Ethernet 10/100/1G
Compression	H.265, H.264, JPEG
Speed	10fps/ch(4MP), 20fps/ch(2MP)
Resolution	Max. 4MP
STORAGE	
Primary/External	2x HDD or (1HDD + 1x eSATA)
SYSTEM	
OS	Embedded Linux (Built-in Flash Memory)
Pre/Post-Alarm	5sec /5sec~5min
Recording Mode	Continuous, Event, Schedule
Data Search	Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time
Backup Interface	USB, Network
Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data
Alarm Action	Buzzer, PIZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push
User	15 Users (Admin, User1 ~User14)
Network Viewer	NETUS-Pro(CMS), NETUS-Lite(RMS), NETUS-Eyes(iOS, Android), NETUS-Infra Server(Optional)
ONVIF	ONVIF Profile S
GENERAL	
Size	340 x 60 x 300 mm
Weight(w/o HDD)	3kg
Temp / Humidity	5°C ~ 40°C /10% ~80%
Power Supply	12V/3.3A
Power Consumption	40 Watts